

375 TRM CIRCLE

CORONA, CA 92879

(951) 256-8555

MATERIAL SAFETY DATA SHEET

May 9, 2006

SECTION I

PRODUCT NAME:

'Weather-All' Brand Polyethylene Film

SIZES:

Various, ranging in thickness between .0004" & .020"

CHEMICAL NAME:

Polyethylene

FORMULA:

(C2H4)n

MANUFACTURER:

T R M MANUFACTURING, INC.

P.O. Box 77520 Corona, CA 92877 375 TRM Circle

Corona, CA 92879

FOR INFORMATION ON HEALTH HAZARDS CALL: 951/256-8555

FOR OTHER INFORMATION CALL: 951/256-8555 INFORMATION EFFECTIVE AS OF: June, 1986

SECTION II—HAZARDOUS INGREDIENTS OF MIXTURES

PRINCIPAL HAZARDOUS COMPONENT(S) Not Applicable

SECTION III----PHYSICAL DATA

BOILING POINT (Degrees F):

Not Applicable.

SPECIFIC GRAVITY (H20=1):

.910 - .925

VAPOR PRESSURE (mm Hg.):

Not Applicable.

PERCENT VOLATILE BY VOLUME (%): Not Applicable.

EVAPORATION RATE:

Not Applicable.

APPEARANCE AND ODOR:

Plastic film, clear or colored, of various

sizes, with little or no odor.

SECTION IV----FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method Used):

Not Applicable.

FLAMMABLE LIMITS:

Not Applicable.

EXTINGUISHING MEDIA:

Water spray, dry chemical, CO2.

SPECIAL FIRE-FIGHTING PROCEDURES:

Self-contained breathing apparatus

and protective clothing should be worn in fighting fires involving chemicals.

UNUSUAL FIRE AND EXPLOSION HAZARD: None.

1

SPECIALIZING IN BUILDING AND AGRICULTURAL POLYETHYLENE SHEETING

8:52 Jan 22 2007 P. 01

Fax:951-256-8575

TRM MANUFACTURING

SECTION V----HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: Not established. EFFECTS OF OVEREXPOSURE: Not Established.

EMERGENCY AND FIRST AID PROCEDURES: If burned by contact with hot plastic, cool molten material adhering to the skin as quickly as possible with cold water, and see a physician for removal of adhering material and treatment of the burn.

SECTION VI----REACTIVITY REPORT

STABILITY: Unstable Stable X

CONDITIONS TO AVOID: Not Applicable. INCOMPATIBILITY (Material to Avoid): Oxidizing materials can cause a reaction. HAZARDOUS DECOMPOSITION PRODUCTS: As with any other organic material, combustion will produce carbon dioxide and probably carbon monoxide.

HAZARDOUS POLYMERIZATION: Will not occur. CONDITIONS TO AVOID: Not applicable.

SECTION VII---SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Collect and contain for salvage/disposal.

WASTE DISPOSAL METHOD: Incineration or landfill. Observe all federal, state and local laws concerning health and pollution.

SECTION VIII—SPECIAL PROTECTION EQUIPMENT

RESPIRATORY PROTECTION: None should be required.

VENTILATION: - LOCAL EXHAUST: If needed to control dust or fumes.

- MECHANICAL (general): Recommended.
- SPECIAL: None known to T.R.M.
- OTHER: None known to T.R.M.

PROTECTIVE GLOVES: Should be worn to protect against thermal burns. EYE PROTECTION: Safety glasses should be worn in any type of industrial operation. OTHER PROTECTIVE EQUIPMENT: Safety shower.

SECTION IX—SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store near heat, flame, or strong oxidants. OTHER PRECAUTIONS: None known to T.R.M.

Health hazard data contained herein was obtained from suppliers of raw materials. Information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them, and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees.

T.R.M. MANUFACTURING, INC.

Ted R. Moore II

Vice-President, Sales Manager

Eax:951-256-8575

p. 03