

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



IDENTITY (As Used on Label and List)

PUMIE SCOURING STICK

Note: Blank spaces are not permitted. If any item is not applicable, or no
information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name

UNITED STATES PUMICE CO.

Emergency Telephone Number

(818) 882-0300

Address (Number, Street, City, State, and ZIP Code)

20219 BAHAMA STREET

Telephone Number for Information

(818) 882-0300

CHATSWORTH, CA. 91311

Date Prepared

Signature of Preparer (optional)

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
-------------------------------------------------------------------	----------	-----------	--------------------------	--------------

PUMICE (VOLCANIC GLASS)

THERE IS NO FREE CRYSTALLINE SILICA PRESENT

Section III — Physical/Chemical Characteristics

Boiling Point	N.A.	Specific Gravity (H ₂ O = 1)	N.A.
Vapor Pressure (mm Hg.)	N.A.	Melting Point	2390° F
Vapor Density (AIR = 1)	N.A.	Evaporation Rate (Butyl Acetate = 1)	N.A.

Solubility in Water

NOT SOLUBLE

Appearance and Odor

ODORLESS SOLID

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used)	N.A.	Flammable Limits	N.A.	LEL	N.A.	UEL	N.A.
Extinguishing Media	N.A.						
Special Fire Fighting Procedures	NONE						

Unusual Fire and Explosion Hazards

NONE

(Reproduce locally)

OSHA 174, Sept. 1985

Section V — Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	NONE
Incompatibility (Materials to Avoid)			NONE
Hazardous Decomposition or Byproducts			
			NONE
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NONE

Section VI — Health Hazard Data

Route(s) of Entry: Inhalation? YES Skin? NO Ingestion? YES

Health Hazards (Acute and Chronic) DRY SAWING OR GRINDING MAY RESULT IN THE RELEASE OF DUST PARTICLES WHICH, ACUTE, MAY CAUSE IRRITATION OF EYES, NOSE OR THROAT AND CHRONIC MAY RESULT IN LUNG DISEASE (SILICOSIS) IF EXPOSED FOR PROLONGED TIME

Garcinogenicity: NTP? NO IARC Monographs? NO OSHA Regulated? NO

Signs and Symptoms of Exposure IRRITATION OF EYES, NOSE & THROAT OR SHORTNESS OF BREATH.

Medical Conditions Generally Aggravated by Exposure PRE EXISTING LUNG DISEASE SUCH AS EMPHYSEMA OR ASTHMA.

Emergency and First Aid Procedures IRRIGATE EYES GENEROUSLY WITH CLEAN WATER FOR 15 MIN. IF IRRITATION PERSISTS, CALL A PHYSICIAN.

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled

SWEEP UP AND PROPERLY DISPOSE

Waste Disposal Method DISPOSE AS COMMON WASTE

Precautions to Be Taken in Handling and Storing NONE

Other Precautions WEAR NIOSH APPROVED RESPIRATOR AND TIGHT FITTING GOGGLES WHEN DRY SAWING OR GRINDING, OR SAW & GRIND WHEN WET

Section VIII — Control Measures (WHEN SAWING OR GRINDING)

Respiratory Protection (Specify Type) NIOSH APPROVED PARTICULATE RESPIRATOR

Ventilation	Local Exhaust	Special
	Mechanical (General)	Other
IN CONFINED AREA		

Protective Gloves WHEN REQUIRED Eye Protection TIGHT FITTING GOGGLES

Other Protective Clothing or Equipment NONE

Work/Hygienic Practices N.A.